

4MP Mini Fixed Bullet Network Camera with Audio

RUCB36-1AX



Key Features



Optics

- Day/night functionality
- Smart IR , up to 98 ft (30 m) IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- 2D/3D DNR (Digital Noise Reduction)
- SD Card

Compression

- Ultra 265,H.265, H.264, MJPEG
- ROI (Region of interest)

Network

- ONVIF Conformance

Structure

- Wide temperature range: -31°F to 140°F (-35°C to 60°C)
- Wide voltage range of $\pm 25\%$
- IP67

Specifications

	RUCB36-1AX
Camera	
Sensor	1/3", megapixel, 4.0 progressive scan, CMOS
Lens	4.0mm@ F1.8
Angle of View(H)	82°
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour:0.01Lux (F2.0, AGC ON) 0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>56dB
IR Range	Up to 98ft (30m) IR range
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream: 4MP (2688*1520), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P(1920*1080), Max 30fps Sub Stream: 4CIF (704*576), Max 30fps; Third Stream: CIF (352*288), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°
HLC	Supported
BLC	Supported
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8 KHZ

Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Smart	
Behavior Detection	Intrusion, Human Body Detection, Motion detection, Tampering alarm, Audio Detection
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	REVO ULTRA Myrevocloud REVO ULTRA REMOTE
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
General	
Power	12 V DC±25%, PoE (IEEE802.3 af)
	Power consumption: Max 6.4 W
Dimensions (L × W × H)	6.5" × 2.5" × 2.5" (165 × 63.1 × 62.5mm)
Weight	0.99 lb (0.45 kg)
Working Environment	-31°F ~ 140°F (-35°C ~ +60°C), Humidity :10%~95% RH(non-condensing)
Ingress Protection	IP67
Surge Protection	2KV

Dimensions

